

# BAT LTE

## Universal Internet & Cellular 4G LTE Alarm Communicator

SKU: IPD-BAT-LTE

Alula's popular BAT-LTE Communicator **is a sunset-free radio**. With IP-first and cell for backup, dealers can retake control over equipment life, getting ahead of a last-minute rush. Position yourself to generate new RMR and provide top-tier customer service, simply with BAT-LTE!

The BAT-LTE Communicator now **bridges app-driven controls and security video** to legacy systems! Dealers can instantly upgrade outdated systems to modern, smart phone-controlled security, easily adding Video Doorbell and indoor and outdoor cameras.



### VIDEO INTEGRATION

Our powerful communicators can be combined with Alula Video



### SIMPLE INSTALLATION



### EASY CELLULAR LTE & INTERNET

Internet connection via Ethernet and pre-activated Cellular LTE



### DUAL HI-GAIN ANTENNAS

Increases Cellular range by up to 50%



### UNIVERSAL PANEL COMPATIBILITY

Works with panels that support Contact ID signaling



### EVENT NOTIFICATIONS

Instant notifications via text/push, email, and computerized voice call



### REMOTE PANEL PROGRAMMING

Eliminate costly truck rolls via remote panel programming



### REMOTE ACCESS ON THE GO

Remotely arm/disarm via Smartphone, Tablet, and PC



connected by  
**verizon**



ALULA



## PANEL COMPATIBILITY

Works with most keyswitch connected panels using CID, including HAI OmniPro, Napco

### Honeywell

Honeywell Vista series panels are fully supported

Vista 10P	Vista 20P/PS/PCN
Vista 10PSIA	Vista 20PI
Vista 128BP	Vista 20PSIA
Vista 128BPE/FB/FBPE	Vista 21IP/IPSIA
Vista 128FBP	Vista 32FB
Vista 128SIA	First Alert FA130
Vista 15	First Alert FA148
Vista 15CN/P/PCN	First Alert FA168
Vista 15PSIA	Safewatch Pro 3000

### DSC

#### Basic Signal only

PC1555  
Alexor  
Impassa  
Neo

#### Full Support

PC1616  
PC1832  
PC1864



#### Basic Signal only

Nx 4v1  
Nx 6v1  
Nx 8v1  
Nx 8E

#### Full Support\*

Nx 4v2  
Nx 6v2  
Nx 8v2

*\*Upload/Download not supported*

## TECHNICAL SPECIFICATIONS

### RADIO:

- Frequencies LTE 4G  
700 MHz/1700MHz/1900MHz

### POWER:

- Externally provided 12v DC
- Typical Current 130 mA
- Max Current 180 mA

### ENVIRONMENTAL:

- Temperature Range  
-30° to +70° C (-22° to +158° F)
- Humidity  
0 to 95% non-condensing

### PHYSICAL:

- Height 7.05 inches
- Width 4.45 inches
- Depth 1.5 inches

