

BAT WIFI

Wi-Fi & Internet Alarm Communicator

SKU: IPD-BAT-WIFI

Alula's universal, dual-path Internet alarm communicator, the BAT WIFI, is a cost-effective solution for takeovers and analog line upgrades, featuring fast IP alarm communications and industry-leading remote service capabilities.



VIDEO INTEGRATION

Our powerful communicators can be combined with Alula Video



SIMPLE INSTALLATION



EASY WI-FI INTERNET



UNIVERSAL PANEL COMPATIBILITY



EVENT NOTIFICATIONS VIA TEXT/PUSH, EMAIL AND VOICE



REDUCE SERVICE COSTS VIA REMOTE PANEL PROGRAMMING



REMOTELY ARM/DISARM VIA SMARTPHONE, TABLET AND PC



UPLOAD/DOWNLOAD WITH SUPPORTED PANELS



ALULA



PANEL COMPATIBILITY

Works with most keyswitch connected panels using CID, including HAI OmniPro, Napco

Honeywell

Honeywell Vista series panels are fully supported

Vista 10P	Vista 20P/PS/PCN
Vista 10PSIA	Vista 20PI
Vista 128BP	Vista 20PSIA
Vista 128BPE/FB/FBPE	Vista 21IP/IPSIA
Vista 128FBP	Vista 32FB
Vista 128SIA	First Alert FA130
Vista 15	First Alert FA148
Vista 15CN/P/PCN	First Alert FA168
Vista 15PSIA	Safewatch Pro 3000

DSC

Basic Signal only

PC1555
Alexor
Impassa
Neo

Full Support

PC1616
PC1832
PC1864



Basic Signal only

Nx 4v1
Nx 6v1
Nx 8v1
Nx 8E

Full Support*

Nx 4v2
Nx 6v2
Nx 8v2

**Upload/Download not supported*

TECHNICAL SPECIFICATIONS

RADIO:

- Wi-Fi
802.11 bg (mixed mode)

POWER:

- Externally provided 12v DC
- Typical Current 130 mA
- Max Current 180 mA

ENVIRONMENTAL:

- Temperature Range
-30° to +70° C (-22° to +158° F)
- Humidity
0 to 95% non-condensing

PHYSICAL:

- Height 7.05 inches
- Width 4.45 inches
- Depth 1.5 inches

SECURITY PROTOCOLS SUPPORTED:

- WPA
- WPAII
- WEP



ALULA

2340 Energy Park Drive, Suite #100, St. Paul, MN 55108 • 1-888-88-ALULA • WWW.ALULA.NET