

Range Extenders

No two installations are alike. For larger, more challenging installs, standard wireless range may not cut it. Extend the functional range of your Touchpads and Connect+ sensors with Alula's **repeaters**. Protect homes and businesses quickly and easily, no matter the size.



Connect+ Sensor Repeater RE620

Alula's Connect+ Sensor Repeater provides batterybacked extension of Connect+ sensors. Extending coverage ensures proper sensor signal strength, preventing costly service calls.

- Extends Range of Connect+ Wireless Sensors
- Rechargeable backup battery
- Cover and Wall Tamper
- 5-year Warranty



Touchpad Range Extender RE621

Large properties demand multiple points of interaction with the system, which can push the limits of wireless range. Extend your reach with the Touchpad Range Extender, ensuring access is available, wherever it's needed.

- Wireless Range Extension
- Single Button Enrollment
- 5-year warranty



TECHNICAL SPECIFICATIONS

RE620 RE621

Physical		
Housing Dimensions	8.5 x 5.0 x 1.3 in (21.6 x 12.5 x 3.3 cm)	8.5 x 5.0 x 1.3 in (21.6 x 12.5 x 3.3 cm)
Weight with Battery	16 oz (454 g)	10 oz (284 g)
Mounting Fasteners (not included)	#4 or #6 screws	#4 or #6 screws
Environmental		
Operating Temperature	32°F to 120°F (0°C to 49°C)	32°F to 120°F (0°C to 49°C)
Maximum Humidity	85% non-condensing relative humidity	85% non-condensing relative humidity
Power		
12VDC Output	10.2VDC to 13VDC, 150mA Max	10.2VDC to 13VDC, 150mA Max
Battery Specifications	6VDC 800mAh NiMH	6VDC 800mAh NiMH
Power Transformer Input Output Part Number	100-240VAC 50/60Hz 0.5A 12VDC 1A RE012-6	100-240VAC 50/60Hz 0.5A 12VDC 1A RE012-6
Current Draw	15mA (Nominal)	15mA (Nominal)
Transmitted Indications	Low Battery, Cover Tamper, Wall Tamper, Supervision	Low Battery, Cover Tamper, Wall Tamper, Supervision
Certification		
Certification Listings	RE620: FCC, IC	RE621: FCC, IC

Specifications subject to change without notice.

